

ROADWORKS BEACON




STANDARD VERSION
RECYCLED HIGH-DENSITY POLYETHYLENE (HDPE)



HEAVY-DUTY VERSION
VIRGIN HIGH-DENSITY POLYETHYLENE (HDPE)



CONVENIENT HANDLE



HIGHLY REFLECTIVE SHEETINGS



COMPANY NAME OR LOGO



Advantages +



HIGHLY REFLECTIVE SHEETINGS

Engineering-Grade (RA1)
High-Intensity Prismatic Grade (RA3).



DIRECTIONAL ARROW

Will help you to position the beacon in the correct direction.



CONVENIENT HANDLE

Easy to carry and install.



COMPANY NAME OR LOGO

Can be moulded-in for easy identification.




STACKABLE DESIGN WITH NOTCHES

Stays in place when stacked, easy to store.

TYPES	OVERALL DIMENSIONS	REFLECTIVE SHEETING DIMENSIONS	REFLECTIVE SHEETING TYPES
Standard Version	Hight: 1300 mm (51") Width: 280 mm (11") Base (foot): 60 × 60 mm (2.4" × 2.4")	Hight: 1000 mm (39") Width: 250 mm (10")	Engineering-Grade (RA1) High-Intensity Prismatic Grade (RA3)
Heavy-duty Version			

BEST SELLERS



6-3-102, 27 Pingxiang road,
266011 Qingdao, CHINA



contact@sinoconcept.co.uk
www.sinoconcept.co.uk